

# Specifications

Model	S-60	S-65
Height, working maximum	66 ft 20.1 m	71 ft 21.6 m
Height, platform maximum	60 ft 18.3 m	65 ft 19.8 m
Height, stowed maximum	9 ft 2.74 m	9 ft 2.74 m
Horizontal reach maximum	51 ft 3 in 15.6 m	56 ft 4 in 17.2 m
Width	8 ft 2.43 m	8 ft 2.43 m
Length, stowed	27 ft 2 in 8.3 m	30 ft 10 in 9.4 m
Maximum load capacity 6 foot platform	600 lb 272 kg	500 lb 227 kg
Maximum load capacity 8 foot platform	500 lb 227 kg	500 lb 227 kg
Maximum load capacity 6 foot platform with foam-filled tires and proper counterweight configuration	750 lb 340 kg	N/A N/A
Wheelbase	9 ft 0 in 2.7 m	9 ft 0 in 2.7 m
Turning radius (outside)	22 ft 2 in 6.75 m	22 ft 2 in 6.75 m
Turning radius (inside)	12 ft 1 in 3.7 m	12 ft 1 in 3.7 m
Turntable rotation (degrees)		continuous
Turntable tailswing	3 ft 3 1/2 in 100 cm	3 ft 3 1/2 in 100 cm
Power source (choice)	Ford 63 Hp Gasoline/LPG LRG-423 or LRG-425 EFI Deutz 56 Hp Diesel F4L 1011	
<b>Drive speeds</b>	<b>2WD</b>	<b>4WD</b>
Drive speed, stowed	4.4 mph	3.0 mph
Gasoline/LPG models	7.1 km/h	4.8 km/h
	40 ft/6.2 sec 12.2 m/6.2 sec	40 ft/9.1 sec 12.2 m/9.1 sec
Drive speed, stowed Deutz Diesel models	4.0 mph 6.4 km/h	2.8 mph 4.5 km/h
	40 ft/6.8 sec 12.2 m/6.8 sec	40 ft/9.7 sec 12.2 m/9.7 sec
Drive speed, raised or extended - all models	0.6 mph 1.0 km/h	0.6 mph 1.0 km/h
	40 ft/40 sec 12.2 m/40 sec	40 ft/40 sec 12.2 m/40 sec

Model	S-60	S-65
Controls	12V DC proportional	
Platform dimensions, 6 foot (length x width)	72 in x 30 in 1.8 m x 76 cm	72 in x 30 in 1.8 m x 76 cm
Platform dimensions, 8 foot (length x width)	96 in x 36 in 2.4 m x 91 cm	96 in x 36 in 2.4 m x 91 cm
Platform leveling	self-leveling	self-leveling
Platform rotation	160°	160°
AC outlet in platform	standard	standard
Hydraulic pressure (maximum) (boom functions)	2600 psi 179 bar	2900 psi 200 bar
Tire size	15-19.5 NHS	15-19.5 NHS
Gradeability, stowed (2WD/4WD)		28% / 40 %
Ground clearance	12 in 30 cm	12 in 30 cm
Hydraulic tank capacity	45 gallons 170 liters	45 gallons 170 liters
Fuel tank capacity	30 gallons 114 liters	30 gallons 114 liters
Weight	26,060 lbs 11,821 kg	28,400 lbs 12,882 kg
Airborne noise emissions		80 dB
Maximum sound level at normal operating workstations (A-weighted)		

**Continuous improvement of our products is a Genie policy. Product specifications are subject to change without notice or obligation.**

