SLAB SCISSOR LIFTS



- Self-propelled electric scissor lifts
- Compact and robust
- Roll-out extension decks for extra reach
- 1.16m wide models rated for outdoor use
- Ideal for construction and maintenance applications



SLAB SCISSOR LIFTS S2632E/2646E/3246E

DIMENSIONS	\$2632E	\$2646E	\$3246E
Max. working height	10.0m	10.0m	11.8m
Max. platform height (A)	8.0m	8.0m	9.75m
Platform size (stowed)	0.74m x 2.31m	1.14m x 2.38m	1.14m x 2.38m
Platform size (extended)	0.74m x 3.22m	1.14m x 3.30m	1.14m x 3.30m
Deck extension length (B)	0.91m	0.91m	0.91m
Overall width (C)	0.81m	1.16m	1.16m
Stowed length (D)	2.37m	2.54m	2.54m
Stowed height (E)	2.33m	2.36m	2.51m
Stowed height (guardrails folded)	1.93m	1.67m	1.82m
Wheelbase	1.92m	1.9m	1.9m
Ground clearance (stowed)	63mm	101mm	101mm
Ground clearance (elevated)	19mm	25mm	25mm

PERFORMANCE				
Platform capacity (SWL)	227kg	454kg	317kg	
Max. operating wind speed (1 person on platform)	Om/s	12.5m/s	12.5m/s	
Max. drive height	8.0m	7.90m	9.75m	
Max. drive speed (elevated)	0.6km/h	0.8km/h	0.8km/h	
Max. drive speed (stowed)	3.2km/h	3.2km/h	3.2km/h	
Raise/lower time	20/26sec	35/60sec	50/60sec	
Gradeability	25%	25%	25%	
Inside turning radius	0.25m	0.25m	0.25m	
Outside turning radius	2.34m	2.5m	2.5m	
Tyres	38.1cm x 12.7cm non-marking solid rubber			
Controls	one-hand proportional joystick			
Drive system	dual front wheel hydraulic motors			


POWER


Power source


24V 4hp DC electric motor 4 x 6V 240 Ah batteries


WEIGHT			
Gross weight	2,224kg	2,359kg	3,003kg

TURNING RADIUS









STANDARD FEATURES

- Proportional controls
- 0.9m extension deck
- Tilt alarm
- Swing-out service trays
- Approved for outdoor use with one person on platform (S2646E/S3246E)
- Power line to platform (no sockets)
- Horn
- Hour meter
- CE approved

OPTIONS

- Special paint colours
- Flashing amber beacon
- Airline to platform
- Dual lanyard anchorage points



Vigo Centre, Birtley Road, Washington, Tyne & Wear, NE38 9DA, U.K. www.snorkellifts.com

t: +44 (0) 845 1550 057 e: sales@snorkellifts.com

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate Snorkel operators manual for detailed instructions on the proper use and maintenance.