



QINGDAO EVERUN MACHINERY CO., LTD.

SKID STEER LOADER

ERS65



3400kg
Operating Weight



0.5-0.6m³
Bucket Capacity



2.9L
Displacement



3490x1820x2150mm
Overall Dimension



- Hydrostatic transmission system, can use different attachments and for many kinds of work.
- The competitive price that makes you!
- 360 degrees steering, it can work flexibly anywhere, even narrow condition.
- Adapt hydraulic leveling system, can keep the bucket balance during lifting and down.
- Option EURO V emission standard.
- The machine operating system adapts mechanic handler, easy for maintenance.

SKID STEER LOADER

ERS65



SPECIFICATION:

Rated Operating Capacity	950kg
Tipping Load	1900kg
Bucket Capacity	0.5-0.6m ³
Operating Weight	3400kg
Max. travel Speed	12km/h
Hydraulic Pump Flow	75L/min
Fuel Tank Capacity	90L
Tires	12/16.5NHS
Overall Dimensions	3490×1820×2150mm

DIMENSIONS

Height at Maximum Extension	4070mm
Height to Bucket Hinge Pin	3100mm
Width with Bucket	1880mm
Track Width	1500mm
Wheelbase	1085mm
Ground Clearance	200mm
Dump Angle	30°
Dumping Height	2450mm
Rollback at Ground	26°

ENGINE:

Model	YunneiDEF20
Net Power	55kW/1800rpm
Type	4 Cylinder in-line, Water cooled, 4 stroke, Diesel engine
Displacement	2.9L

STANDARD

Deluxe Enclosed Operator cab
Hydraulic Joystick Controls
Standard Bucket
Auxiliary Hydraulic Couplers

OPTIONAL

Preheat Starting Assist System for Extreme Cold Cab
Fitted with a Heater as Standard
Air Conditioner
2-speed Transmission System